



Strato 101

Wood Filler Bonding Agent, water based

- ◆ Quick drying
- ◆ Good filling ability
- ◆ Easy to use

Substrate:

Suitable for all types of wood, in a dry, oil, wax and dust free condition.

Application Notes:

Mix with clean sanding dust, from the last sanding stage to a trowelable mass. Only apply using a stainless steel trowel. or plastic

Coating:

Once sanded, any of the Eukula products may be applied to the substrate.

Drying:

Strato 101: 30 – 90 min.
According to the temperature and air humidity.

Consumption:

Ca. 50 – 100 g/m², according to the quantity and the size of the joint.

Cleaning of Tools:

Immediately after use with water.

Storage:

Store in cool and dry conditions. The material can be stored in the original containers for up to 12 months. Protect from frost.

Hazardous Goods Marking:

GefStoffV:	Not applicable
VbF:	Not applicable
ADR/RID:	Not applicable
UN-No.:	Not applicable
Giscode:	W 1
R-Terms:	None
S-Terms:	38 In case of insufficient ventilation, wear suitable respiratory.
	23 Do not breathe spray.

Disposal:

The material should not be allowed to enter water courses, dried material can be treated as normal waste.

Product-Number: 500019

Date: 20.06.06

Revision date: 07.12.05

page: 1/5

1. Identification of the preparation and company

Product Name and Code: 500019 STRATO 101
Wood Filler, water based

Recommended intended purpose: Industrial Coating

Name of the company:

Eukula GmbH
Am Bahnhof 6
D-78199 Bräunlingen

Phone +49(0)7707/151-206 or 248
Fax +49(0)7707/151-245
E-Mail Vertrieb@eukula.de

Information-giving Area:

Productsecurity

Emergency phone: +49(0)7707/151-0

2. Composition/Information on ingredients

Chemical characteristic: Preparation based on watery
modified carbohydrate

Dangerous substances:

ELNECS-No.	Name	Symbol	Conc.%
CAS-No.	R phrases		
171054-89-0	Säureaddukt von 4-oxo-4-p-tolylbutyrat u. 4-ethylnitrophenol	Xi	0.5 < 2.5

(See full text of R phrases under chapter 16)

3. Hazards identification of the preparation

Danger designation: not applicable

Special dangers for humans and environment:
not applicable

4. First aid measures**General :**

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation :

Remove to fresh air, keep patient warm and at rest, if breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

Eye contact :

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact :

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.

Product-Number: 500019

Date: 20.06.06 Revision date: 07.12.05

page: 2/5

Ingestion :

If accidentally swallowed obtain immediate medical attention. Keep at rest.
Do not induce vomiting.

5. **Fire-fighting measures**

Extinguishing media: recommended: alcohol resistant foam,
CO₂, powders, waterspray
not to be used : waterjet

Recommendations: Due to the organic solvents' content of the preparation, fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

6. **Accidental release measures**

Due the organic solvents' content of the preparation :
Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8. Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses.

Clean preferably with a detergent; avoid use of solvents.
If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

7. **Handling and storage**

Handling

Due the organic solvents' content of the preparation :
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid to vapour concentration higher than the occupational exposure limits.
Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
Keep container tightly closed. Isolate from sources of heat, sparks and open flame. No sparking tools should be used.
Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.
Smoking, eating and drinking are forbidden in application area.
Comply with the health and safety at work laws.
Always keep in containers of same material as the original one.
For personal protection see Section 8.
Never use pressure to empty : container is not a pressure vessel.

Storage

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight.
Due the organic solvents' content of the preparation :
Keep away from sources of ignition. Keep away from oxidising agents, from strongly alkaline and strongly acid materials.
No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Product-Number: 500019

Date: 20.06.06

Revision date: 07.12.05

page: 3/5

8. Exposure controls/personal protection**Engineering Measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Exposure Limits

Occupational exposure limit for :

EINECS-No.	Names	STEL	LTEL

Personal Protection

European Union guidelines and BG rules of the professional associations considers.

Respiratory protection:

If the concentration is because of organic solvents, gases and steams over the job limit values, then a respirator certified for this purpose must be carried (type of gas filter A, identification colour code brown), e.g. half mask FFA2 to be carried.

Hand protection:

Wear suitable safety gloves with the work. Suitably a chemical protection glove examined after DIN/EN 374 is e.g. glove material: Nitrile rubber, Latex, PVC material thickness $\geq 0,4\text{mm}$, break-through time: ≥ 30 min. contaminated and worn out gloves have to be replaced. The user has to examine and consider the applicability of the selected safty gloves in accordance with the instructions and the information of the glove manufacturers for the individual use conditions. Missing skin fat is to replace by containing

Eye protection:

Use safety eyewear designed to protect against splash of liquids.

Skin protection:

All parts of the body should be washed after contact.

9. Physical and chemical properties

form : liquid

colour: see under point 1 "Product Name a. Code"

smell : typical

	value	method
flash point:	> 100 °C	--
viscosity:	20-25 P./Sp.1 by 20 °C	cup
specific gravity:	0.97 g/cm ³ by 20 °C	--
lower explosion limit:	0.8 Vol.%	--
upper explosion limit:	not applicableVol.%	--
solubility in water:	soluble in water	
boiling point:	100 °C	literature value
vapour pressure:	not applicablembar by 20 °C	liter.value
pH-value:	not applicable	
ignition temperature:	not applicable°C	literature value
solvent content(org.):	0 approx./by weight	
water content:	63 approx./by weight	

Product-Number: 300019

Date: 20.06.05

Revision date: 07.12.05

page: 4/5

10. Stability and reactivity

Stable under recommended storage and handling conditions. (See section 7)
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

11. Toxicological information

There are no data available on the preparation itself.
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.
Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

There are no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.
The preparation was evaluated on the basis the conventional method of the preparing guideline (1999/45/EG) and was not classified as environmental dangerous.

13. Disposal considerations

Do not allow into drains or water courses.
Empty containers are to be deposited according to the official rules.
Dispose of in accordance with applicable local, state and federal regulations.

14. Transport information

Transport only in accordance with ADR for road, RID for rail, IMDG for sea and ICAC/IATA for air transport.

ADR/RID:
ADR-RID-Class: not applicable
Tremcard: not applicable
UN-Number: not applicable
Transport document name:
item:
Packaging group: not applicable

Product-Number: 500019

Date: 20.06.06

Revision date: 07.12.05

page: 5/5

IMDG:
IMDG-Class: not applicable
Tremcard: not applicable
EnS: not applicable
UN-Number: not applicable
Packaging group: not applicable

Marine pollutant: not applicable

ICAO/IATA:
ICAO/ IATA-Class: not applicable
UN-Number: not applicable

Packaging group: not applicable

15. Regulatory information

The requirements of the Classification Packaging and Labelling of Dangerous Substances Regulations.

The product is labelled as follows :

Danger classification :

Contains:
not applicable

R-phrases:
not applicable

S-phrases:
not applicable

other phrases:
not applicable

16. Other information

Full text of R phrases appearing in section 2 :

41 Risk of serious damage to eyes.

The information of this MSDS is based on the present state of our knowledge and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction.

It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this MSDS is meant as a description of the safety requirements of our product; it is not to be considered as a guarantee of the products' properties. The statements given in the safety data sheets of our product groups are average values as they depend on the colour shade.

The information in this Safety Data Sheet is required pursuant to Dangerous Substances Regulations 26.10.1993.
